Eliment® insulation

- **Dual thermal and acoustic glasswool insulation**
- **Thermal performance independently verified to NZ standards**
- **CodeMark and EUCEB certified**
- **Made using up to 80% recycled glass**
- **GreenTag Level A certified**
- **EECA Healthy Homes and Kāinga Ora approved**
- **Compressed up to 15x at packaging to reduce transport and CO2 emissions**
- **70 year product Warranty**
- **Listed online with MasterSpec, Smartspec and Design Navigator for H1 Calculations**
- **Available to order nationwide from professional installers, PlaceMakers, ITM and other selected building merchants**

CodeMark CERTIFIED
CMNZ70114

elimentinsulation.co.nz

Eliment® insulation

Eliment is designed for a wide range of wall, ceiling, mid-floor and skillion applications. It is manufactured using recycled glass and employs a phenolic resin-based binder that incorporates a natural anti-formaldehyde ingredient. The Eliment insulation range encompasses multiple densities, thicknesses and dimensions.

Wall Insulation Product Specifications

R-Value (m2 K/W)	Thickness (mm)	Width (mm)	Length (mm)	Piece per Pack	Packs per MasterBag	Area Per Pack (m2)	Approx. Cover. per Pack (m2)[2]
R1.8 Wall	75	600	1200	20	8	14.40	14.40
R2.2 Wall	90	580	1140	16	8	10.58	12.47
R2.4 Wall	90	560	1140	13	8	8.30	9.85
R2.6 Wall	90	560	1140	11	8	7.02	8.26
R2.8 Wall	90	560	1140	7	8	4.47	5.24
R3.2 Wall	140	560	1140	13	8	8.30	9.77
R3.6 Wall	140	560	1140	9	8	5.75	6.82
R4.1 Wall	140	560	1140	6	8	3.83	4.51
R4.3 Wall	140	560	1140	4	8	2.55	3.01

Ceiling and Skillion Insulation Product Specifications

R-Value (m2 K/W)	Thickness (mm)	Width (mm)	Length (mm)	Piece per Pack	Bales per MasterBag	Area Per Pack (m2)	Approx. Cover. per Pack (m2)
R3.6 Ceiling [1]	165	432	1220	14	8	7.38	7.68
R4.2 Ceiling	195	432	1220	12	8	6.32	6.62
R5.3 Ceiling	230	432	1220	8	8	4.22	4.39
R6.3 Ceiling	278	432	1220	7	8	3.69	3.84
R7.3 Ceiling	285	460	1220	5	8	2.81	2.73
R3.2 Skillion	115	560	1220	9	8	6.15	6.64
R5.0 Skillion	165	560	1220	4	8	2.73	2.95
R6.0 Skillion	215	560	1220	5	8	3.42	3.69
R7.4 Skillion	265	560	1220	4	8	2.73	2.95

[1] R3.6 Ceiling is specifically suited to mid-floor applications for combined thermal and acoustic performance, with R2.6 Wall, R2.8 Wall and R4.2 Ceiling also suitable. Double layer of R3.6 = R7.0 (refer to Codemark Certificate).

[2] Approx. coverage per pack relates to standard structures (i.e. with framing allowance) therefore actual coverage may vary.

Technical specifications shown are intended to be used as general guidelines only. The physical and chemical properties of glasswool insulation listed represent typical average values obtained in accordance with accepted test methods and are subject to normal manufacturing variations. They are supplied as a technical service and are subject to change without notice. Warranty shall be in accordance with General Terms and Conditions. No responsibility is assumed for the correctness of this information. May. 2026